



PRODUCT-DETAILS

5333GR
3/4 INSUL GRND LIQUIDTIGHT STRAIGHT



General Information	
Extended Product Type:	5333GR
Product ID:	7TAD012300R0004
EAN:	5414363143147
Catalog Description:	3/4 INSUL GRND LIQUIDTIGHT STRAIGHT
Long Description:	3/4 Inch Steel External Bonding Liquidtight Insulated Connector Flexible Metal Conduit Fitting, Straight, With Revolver Lug, With Tin Plated Copper Alloy Lug for Awg #14 to #2 Ground Wire, for Use In Wet Locations, 25 Pieces
Display Name:	5333GR

Eco Transparency	
Environmental Product Declaration - EPD:	9AKK108470A5001

Additional Information	
Application:	To positively bond conduit to box or enclosure
Product Type:	Grounding Connectors-Straight

Ordering

EAN:	5414363143147
UPC:	786210899992

Technical

Number of Batteries:	0
Material:	Steel
Size:	3/4 Inch

Environmental

WEEE Category:	Product Not in WEEE Scope
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units:	25 EA
Package Level 1 Height:	134.62 mm 5.3 in
Package Level 1 Depth / Length:	175.26 mm 6.9 in
Package Level 1 Width:	147.32 mm 5.8 in

Certificates and Declarations

Data Sheet, Technical Information:	TDS000120
------------------------------------	-----------

External Classifications and Standards

ETIM 8:	EC001180 - Screw connection for protective metallic hose
ETIM 9:	EC001180 - Screw connection for protective metallic hose
UNSPSC:	39121420

Categories

Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Liquidtight Fittings > T&B Liquidtight

